Perfect OLac STOCK COLLECTION MATERIAL 2024

Properties and technical characteristics of Perfect Lac surfaces.

N°	Characteristic	Norm reference	Value/Result				
1	Gloss	1	2,5 gloss (incidence angle 60°)				
2	Adhesion/crosshatching	UNI EN ISO 2409: 2013	0 (scale ISO)				
3	Resistance to dry heat	UNI EN 12722: 2013	Class B (following CEN/TS 16209, 140°C liv. 4)				
4	Resistance to moist heat	UNI EN 12721: 2013	Class B (following CEN/TS 16209, 85°C liv. 5)				
5	Tendency to retain dirt	UNI 9300: 2015	Level 5				
6	Resistance to cold liquids	UNI EN 12720: 2013 substances group following CEN/TS 16209	Contact time: 16hAcetic acid 10%rating 5Waterrating 5Alcohol et. 48%rating 5Ammonia 10%rating 4Coffeerating 5Detergent solutionrating 5				
7	Resistance to scratches	UNI EN 15186:2012 method B	2,9N (etching on the paint film)				
8	Resistance to light UNI 9427	UNI EN 15187:2007	Grade >4 (gray scale) Grade >6 (woolblau scale)				

Upon request, it is possible to apply on Perfect Lac surfaces an antiseptic finishing, following norm ISO22196:2011, which permits a reduction on antibacterial activity of 99,9%, granting the maximum cleanliness and hygiene of the product; the antibacterial treatment persists until lacquering removal.

All the stock materials of Perfect Lac Stock Collection are always supplied with protection film so to allow further handling and working processes.

Properties and technical characteristics of the support.

For the production of all the colours of Stock Collection the material used is MDF panel, certified CARB P2; different support materials can be used, on condition of an engagement of consumption.

All the panels used are certified following the Custody Chain FSC-CoC.

Upon request, on condition of engagement of consumption, the panel used can be certified HYDRO

Exclusions

Any other different mandatory requirements, necessary for the nation of destination or for the use of the product, must be evaluated time by time with the Clients.



Stock synthesis for plain colours

	PANEL									EDGE		Color reference (**)
Code	Colour	Cat. Price	Q.ty pack (*)	Туре	CARB P2	FSC CoC	IDRO	Dimension (mm)	Thickness (mm)	Туре	Q.ty (ml)	
001	Bianco	1	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL9016
002	Taupe	2	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	PANT. Warm gray 4
003	Ardesia	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL7012
004	Marine blue	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	PANT. 4139 C
005	Green alga	2	25 panels	MDF	Х	Х		2.800x1.220	19-22	Abs 10/10	150ml	RAL7010
006	Wine	3	25 panels	MDF	Х	Х		2.800x1.220	19-22	Abs 10/10	150ml	RAL3005
007	Nero	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL9011
008	Mineral grey	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL7039
009	Lino	2	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL1019
010	Grigio perla	2	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	RAL7047
011	Piombo	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19-22	Abs 10/10	150ml	PANT. Cool Gray 10 C
012	Bianco Latte	1	25 panels	MDF	Х	Х	Х	2.800x1.220	19	Abs 10/10	150ml	RAL 9001
013	Grigio Nuvola	3	25 panels	MDF	Х	Х	Х	2.800x1.220	19	Abs 10/10	150ml	RAL 7037
014	Terracotta	3	25 panels	MDF	Х	Х		2.800x1.220	19	Abs 10/10	150ml	PANT. 4014 C
015	Salvia	3	25 panels	MDF	Х	Х		2.800x1.220	19	Abs 10/10	150ml	PANT. 4178 C
016	Foresta	3	25 panels	MDF	Х	Х		2.800x1.220	19	Abs 10/10	150ml	PANT. 18-5616TPX
017	Brique	3	25 panels	MDF	Х	Х		2.800x1.220	19	Abs 10/10	150ml	PANT. 18-1449TPX



Stock synthesis for woodgrain veneered finishing

PANEL									EDGE		Color reference (**)	
Code	Colour	Cat. Price	Q.ty pack (*)	Туре	CARB P2	FSC CoC	HYDRO	Dimension (mm)	Thickness (mm)	Туре	Q.ty (ml)	
PW 001	Noce Canaletto		25 panels	Chipboard	Х	Х		2.800x1.220	19-22	Abs 10/10	150ml	
PW 002	Rovere Europeo		25 panels	Chipboard	Х	Х		2.800x1.220	19-22	Abs 10/10	150ml	
PW 003	Rovere rigato laccato Bianco		25 panels	Chipboard	Х	х		2.800x1.220	19-22	Abs 10/10	150ml	

(*): panels supplied with protection film on the lacquered side and packed on wooden crossbars with coverboards to return; for orders under 25 panels we will debit a packing surcharge of € 40,00 each coil.

(**): the indicated colour correspondence is approximate and not binding.

Upon request the panels can be edged in bars with the following profiles:

- slab bar

- J-pull bar

- U-pull bar

- K bar

The indicated price categories are valid for orders from 1 coil per colour. Following surcharges are applied for different quantities:

- orders for 5<25 panels per colour:
- orders for less than 5 panels per colour:

surcharge 30% surcharge 50%